

The smallest laser-based 5-diff hematology analyzer with open tube sampling

- Complete Blood Count results in one minute
- Easy to use, straightforward navigation
- Extremely small footprint, reagent consumption and sample volume processing
- Point-of-Care testing possibilities:
 ICU, ER, Mobile Care Units
- Possibility to measure from capillary samples
- Minimal user maintenance
- Remote Access: online diagnostic tool



norma

Technical Specifications

Reference number NO50H

27 Parameters WBC, LYM, MON, NEU, EOS, BAS, LYM%, MON%, NEU%, EOS%, BAS%, NLR,

RBC, HGB, HCT, MCV, RDWsd/cv, MCH, MCHC, PLT, MPV, PCT, PDWsd/cv, PLC-R%, PLC-C

Measurement technology Laser based forward-scattered light detection for WBC

Volumetric impedance method for RBC

Photometric method for HGB

Scattergram, Histograms WBC 5-part scattergram and RBC, PLT histograms

Sampling mode Open tube sampling Aspirated sample volume $38 \mu l$ whole blood Processed sample volume $2 \times 1.4 \mu l$ whole blood

Throughput 57 tests / hour

Precision (CV%) WBC < 3%, RBC < 2%, PLT < 5% MCV < 1%, HGB < 2%

Storage capacity 40,000 test results incl. scattergram, histograms and patient data

User interface LCD, 10.1", 1280 × 800 with capacitive touchscreen, portrait

Connectivity 2 x USB ports, Ethernet, LIS (HL7 and ASTM)

Dimensions 280 x 216 x 336 mm

Weight 8.5 kg

Reagents Norma-iDil5 OP, Norma-iLyse5 OP, Norma-iClean5 OP

Optional Detergents Norma-iHClean, Norma-iOptiClean



Icon-5 OP combines a cutting edge technology and environmentally friendly innovations with a fresh and award-winning design







Norma/Instruments Zrt.

Papírgyár u. 58-59., 1038 Budapest, Hungary +36 1 815 4370; office@normadiagnostika.com

Norma Instruments Zrt. reserves the right without notice to make any technical changes it considers necessary or desirable.